

esko®

eflare™

safety in a flash

EFLARE INTRINSICALLY SAFE LED EMERGENCY BEACON

AT280 - (Colour) (15cm)
AT290 - (Colour) (20cm)

Latest generation beacons, lighter & brighter.



IECEx and ATEX
Accredited—Ex ic IIC
T4 Gc IP66

Eflare provides a quick
and easy method to
enhance safety by
creating a highly visible
warning or safety zone

Conspicuous for more
than 1 kilometre at night

Extremely compact and
lightweight for easy
deployment

Waterproof, dustproof—
will survive a 1 metre drop
onto concrete

Clear Fresnel lens
with specialised high
performance design/360
visibility

20+ hours battery life,
takes 4x AA batteries
(not included)



PERFORMANCE FEATURES

- + IECEx and ATEX Accredited—Ex ic IIC T4 Gc IP66
- + Eflare provides a quick and easy method to enhance safety by creating a highly visible warning or safety zone
- + Conspicuous for more than 1 kilometre at night
- + Extremely compact and lightweight for easy deployment
- + Waterproof, dustproof—will survive a 1 metre drop onto concrete

- + Clear Fresnel lens with specialised high performance design/360 visibility
- + 20+ hours battery life, takes 4x AA batteries (not included)
- + Stocked colours: Red, Amber, Blue, White
- + Red/blue and red/white dual colour combinations available on indent (restricted uses)
- + Height: 20cm (AT290), 15cm (AT280)
- + Flash Rate: 165-185fpm
- + Weight Inc batteries: 260g (AT290), 200g (AT280)

Suitable for

- + Emergency services
- + Hazardous locations
- + Transport operators
- + Rail
- + Aviation & Military
- + Highway/utility maintenance
- + Recovery
- + Mining
- + Forestry



sales@eskosafety.com

0800 500 470

56 Hurlstone Drive, New Plymouth

esko®

LATEST GENERATION BEACONS

Product Range									
Compact Part No	Standard Part No	LED Qty	Function	Candela	Weight (Inc Batteries)	Height	Flash Rate	Battery	Battery Life
AT280R	AT290R	8	Flash or Steady On	Flash = 60 Steady On =20	Compact = 240g Standard = 260g	Compact = 15cm Standard = 20cm	165-185 fpm	4 x AA Cell	20+ Hours
AT280A	AT290A			Flash = 70 Steady On =25					
AT280B	AT290B			Flash = 18 Steady On = 10					
AT280G	AT290G			Flash = 40 Steady On =13					
AT280W	AT290W			Flash = 80 Steady On = 25					
AT 283RB	AT 293RB	4 + 4	Dual Flash	30					
AT 283RA	AT 293RA			35					
AT 283RW	AT 293RW			40					
AT 283RG	AT 293RG			30					
AT 283BW	AT 293BW			40					
AT 283GW	AT 293GW			40					
AT 283AB	AT 293AB			35					
AT 283BG	AT 293BG			20					
AT 283GA	AT 293GA			35					
AT 283AW	AT 293AW			40					

Product Definitions

AT = Flash or Steady On in single colour (flash only in dual flash models)
 TF = Torch option added to either (dual) flash or steady on unit.
 Letter at the end denotes LED colour(s)
 Units come in either Compact height (15cm) or Standard height (20cm)
 Dual flash candela measurements based on the dominant colour

Special Order Products

TF units with torch option
 281 or 291 - single colour flash only
 282 or 292 - single colour steady on only

ACCESSORIES



Rubber Base Mount



Aviation Base Mount



Magnetic Base Mount



Floatation Collar



Cone Mount Clip



Lanyard



sales@eskosafety.com

0800 500 470

56 Hurlstone Drive, New Plymouth